

# INSTRUCTIONS FOR DUNK TANK

## TOWING

1. Always use safety chains when towing the tank; make sure to check the brake lights and turn signals.
2. Make sure that the target frame is folded to the side of tank and attached to cage with rubber straps. (attached to frame) Attach chain to frame and hook to cage.
3. A 2" trailer ball is required.
4. Make sure that hitch secures snug to ball.
5. Hook safety chains to vehicle and hook up lights.
6. Target arm, target plate and balls should be stored in tow vehicle.

## SET-UP

1. A level area needs to be selected for the set-up location.
2. Unhook trailer, safety chains, and lights from the tow vehicle. Roll the Tank to set-up location.
3. Trailer tongue should be removed by taking out pins that attach tongue to trailer. Replace pins in tongue bar. (This should be stored in a safe place away from the Dunk Tank)
4. Carefully lift tank to upright position.
5. Unhook the rubber straps and the chain from the cage and unfold the frame. The chain is now used to secure the frame to the tank unit to keep the frame from pushing forward in a wind. There is a place for a spike to be driven at the bottom of the backstop frame to keep the backstop frame secure.
6. Make sure drain plug is tight before filling with water.
7. The target arm goes behind the bar under the seat; the bolt goes into the bolthole on the frame and then goes through the hole allowed in the tarp. Once this is done the target plate is attached to the end of the target arm that has gone through the tarp hole.
8. Test the target arm by pressing on target plate. If installed correctly the seat should release. To reset the seat, pull up on the front of the seat until you hear the latch lock.
9. Diagram for lights are located on the back of the light fixture.

## OPERATION

1. **NEVER** operate Dunk Tank around electricity.
2. **ADULTS ONLY** to operate and supervise dunk tank.
3. Water level in tank should be kept at least 6" from top of tank.
4. Participants must be at least 5' tall.
5. Only one person allowed on seat or in the tank.
6. Check that seat is secured prior to placing full weight on seat.
7. When tank is not in operation or unattended, always drain the water.
8. **NEVER** stand on the seat.
9. Caution should be taken that participant sit up straight; keep hands on lap; keep legs together.
10. **NEVER** allow participant to hold on to bars or stick feet through bars.
11. Operator only permitted behind tank or target area.
12. Persons who have used drugs or alcohol are **NOT** permitted in tank.
13. Maximum weight limit is 250 pounds.

# HI STRIKER CO.

## 573-265-2100

### Rules for Operation of Dunk Tank

1. **NEVER** operate Dunk Tank around electricity.
2. **ADULTS ONLY** to operate and supervise Dunk Tank.
3. Water level in tank should be kept at least 6" from top of tank.
4. Participants must be at least 5' tall.
5. Only one person allowed on seat or in the tank.
6. Check that seat is secured prior to placing full weight on seat.
7. When tank is not in operation or unattended, always drain the water.
8. **NEVER** stand on the seat.
9. Caution should be taken that participant sit up straight; keep hands on lap; keep legs together.
10. **NEVER** allow participant to hold on to bars, seat or stick feet through bars.
11. Operator only permitted behind tank or target area.
12. Persons who have used drugs or alcohol are **NOT** permitted in tank.
13. Maximum weight limit is 250 pounds.